

# Lucas

Trust Lucas



**Calcium Plus**  
Maintenance Free Battery

# Lucas PREMIUM

# TECHNICAL SPECIFICATION FOR AUTOMOTIVE, JIS & DIN BATTERY

Battery Type		AH @ 20 Hour Rate	CCA	Dimension (mm)			Cell Layout	Terminal Type	Filled Weight (kg)
Old JIS	New JIS			L	W	H			
<b>PASSENGER CAR</b>									
NS40/L	36B20R/L	32	280	197	129	227	1/2	B	8.6
NS40Z/L	44B20R/L	35	335	197	129	227	1/2	B	9.2
N40/L	50B24R/L	40	350	238	129	227	1/2	B	10.8
N40S/LS	50B24R(S)/L(S)	40	350	238	129	227	1/2	A	10.9
NS60/L	55B24R/L	45	440	238	129	227	1/2	B	11.4
NS60S/LS	55B24RS/LS	45	440	238	129	227	1/2	A	11.5
55D23/L	65D23/L	60	550	231	173	225	1/2	A	14.6
N50/L	55D26R/L	50	440	259	173	225	1/2	A	14.2
N50Z/ZL	65D26R/L	60	530	259	173	225	1/2	A	15.6
NS70/L	80D26R/L	65	600	259	173	225	1/2	A	17.0
NX110-5/L	85D26R/L	70	600	259	173	225	1/2	A	17.0
N70/L	85D31R/L	70	635	306	173	225	1/2	A	18.6
N70Z/ZL	95D31R/L	75	650	306	173	225	1/2	A	18.6
NX120-7/L	105D31R/L	80	750	306	173	225	1/2	A	19.9
N90/L	115D31R/L	90	775	306	173	225	1/2	A	20.0


<b>COMMERCIAL VEHICLE</b>									
N100/L	115E41R/L	100	700	410	173	233	1/2	A	25.9
N120/L	135F51R/L	120	850	506	182	250	1/2	A	32.9
N135/L	150F51R/L	135	875	506	182	250	1/2	A	33.7
N150/L	165G51R/L	150	1000	506	221	248	1/2	A	38.0
N170/L	190G51R/L	170	1050	506	221	248	1/2	A	39.7
N180/L	195H52R/L	180	1100	518	274	248	1/2	A	47.0
N200/L	210H52R/L	200	1200	518	274	248	1/2	A	48.0

## HOLD DOWN AVAILABLE FOR FULL RANGE PASSENGER CAR BATTERY


Catalogue	Capacity 20HR	CCA	Dimension (mm)			Cell Layout	Terminal	Hold Down	Filled Weight (kg)
			L	W	H				
54434/54459	44	390	207	175	190	2	1	B13	11.7
55530/55548	55	480	242	175	190	2/1	1	B13	14.0
56030/56031	60	540	242	175	190	2/1	1	B13	14.3
56618/56638	66	580	278	175	190	2	1	B13	16.2
57217/57219	72	680	278	175	190	2/1	1	B13	17.6
57412/57413	74	680	278	175	190	2/1	1	B13	17.6
57512/57513	75	680	278	175	190	2/1	1	B13	17.6
58533/58535	85	700	315	175	190	2	1	B13	19.3
58035/58043	80	700	315	175	190	2	1	B13	19.3
58815/58827	88	800	353	175	190	2	1	B13	20.6
59218/59259	92	800	353	175	190	2/1	1	B13	20.6
60038/60044	100	850	353	175	190	2	1	B13	21.7

<b>LOW HEIGHT SERIES</b>									
54321/54322	43	390	207	175	175	2/1	1	B13	11.0
55046	50	430	242	175	175	2	1	B13	12.8
55419/55457	54	430	242	175	175	2	1	B13	12.8
55506	55	430	242	175	175	2	1	B13	12.8
58014	80	700	315	175	175	2	1	B13	17.7
58515	85	740	353	175	175	2	1	B13	20.1


### JIS Terminal Type :



### Cell Layout :



### DIN Bottom Hold :



### DIN Terminal Type :

